

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 927 649 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
07.07.1999 Bulletin 1999/27

(51) Int. Cl.⁶: **B43M 7/02**, G07B 17/04,
G06F 17/60

(21) Application number: **98204464.6**

(22) Date of filing: **29.12.1998**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **31.12.1997 NL 1007944**

(71) Applicant: **Neopost B.V.**
9201 BX Drachten (NL)

(72) Inventors:
• **Edens, Bertus Karel**
9204 JT Drachten (NL)
• **Hidding, Gerhard**
8447 EJ Heerenveen (NL)

(74) Representativè:
Ottevangers, Sietse Ulbe et al
Vereenigde Octrooibureaux
Nieuwe Parklaan 97
2587 BN 's-Gravenhage (NL)

(54) Registration of documents

(57) Registration of existing, physical documents, comprising: the step of a data processor structure (3, 6; 23) determining a code in each case; actuating a marking assembly (5; 25) for applying a mark, which represents the code, on each document to be registered; the step of the data processor structure (3, 6; 23) actuating registration means in response to the application of the mark; and registering accordingly data corresponding with the code, on a protected information carrier (4; 24). Because it is one and the same data processor structure (3, 6; 23) that carries out the determination of the code, the application of a mark corresponding with the code, and the storage, in a protected memory, of codes of said codes that correspond with applied marks, a safeguard regarding the authenticity of stored data regarding documents is obtained in a highly efficient and reliable manner.




Fig. 1

EP 0 927 649 A1

Description

[0001] This invention relates to a method and a system for registering existing documents.

[0002] It is generally common to register received and sent documents to be able to prove which documents have been received and sent. In doing so, customarily, data regarding documents are registered. Documents, such as incoming mail, are moreover provided with a stamp to indicate that a document has been registered and when it has been registered. Recording the existence of a document and the time when the document has become available is also of importance for other applications, such as for registering declarations such as *procès-verbaux* and for determining the date of transactions.

[0003] Maintaining such an administration is very time-consuming and for many applications such an administration is not sufficiently protected from modification afterwards. Particular problems are proving the authenticity, or at least the authentic contents of documents, proving the time of registration of a document, and proving non-receipt of a document.

[0004] The object of the invention is to provide a solution which makes it possible to enable registering documents in a simpler manner.

[0005] According to the present invention, this object is achieved by providing a system according to claim 1. To this end, the invention further provides a method according to claim 17.

[0006] Because it is one and the same data processor structure that carries out the determination of the code, the application of a mark corresponding with the code, and the storage, in a protected memory, of codes of said codes that correspond with applied marks, a safeguard in respect of the authenticity of stored data regarding documents is obtained in a highly efficient and reliable manner.

[0007] The marking assembly can be designed in many ways, for instance in the form of a printer, a perforator, an embossing station, a branding element or a device for applying labels.

[0008] Particularly advantageous embodiments of the invention and modes of carrying out the invention are set forth in the dependent claims.

[0009] Further objects, embodiments, details and advantages of the invention are apparent from the following description, in which reference is made to the accompanying drawings. In the drawings:

Fig. 1 is a diagrammatic representation of a system according to a first exemplary embodiment of the invention, and

Fig. 2 is a diagrammatic representation of a system according to a second exemplary embodiment of the invention.

[0010] The exemplary embodiment of the invention

shown in Fig. 1 is currently preferred most. This system is suitable for use by a plurality of users each utilizing a client-bound system 1 of the system. Of these client-bound systems, one will be described hereinafter in more detail. The others are basically identical. It is possible that one or more of the client-bound systems in turn consist of a server having connected to it a plurality of stations which can utilize the registration facility of the system according to the invention.

[0011] These client-bound systems 1 are connected via a generally accessible network 2, such as a telephone network, a data transmission network or a combination thereof, with a central data processor 3, which is coupled to a protected data storage 4. The central data processor 3 and the protected data storage 4 are preferably managed by a central certifying authority which guarantees the authenticity of data stored in the data storage 4 and at which authority users can subscribe to the certification of their document registration. Such an authority can be, for instance, a postal organization, a civil-law notary office, or a certification bureau. As a generally accessible network, the network does not form part of the system that is arranged and offered especially for registering documents, even though use is made of it. It is also possible, however, to arrange for the transfer of data between the central processor 3 and the user systems 1, for instance, by the transfer of information carriers such as diskettes, from the client-bound systems 1 to the central data processor *vice versa* or by radio transmission.

[0012] The data processor structure is arranged for generating and issuing codes that can be coupled by users to documents to be registered. The client-bound systems are each made up of at least one marking assembly 5, which is coupled to a local data processor 6, which is coupled to the central data processor via a suitable local interface 7, such as a modem or an adapter, and a suitable central interface 8, such as a system of modems and/or adapters. The central data processor and the distributed local data processors together form a data processor structure which issues the codes to be used and registers codes which have been used. For operating the local data processor 6, the marking assembly 5 and for managing communication with the central data processor 3, the local data processor 6 is coupled to an operating interface consisting of a keyboard 9 and a display 10.

[0013] The marking assembly 5 and the local data processor 6 are arranged and coupled for providing each document to be registered with at least one mark which represents one of the generated codes and for generating, in response to the application of a code, instruction signals for registering codes used. Sending those instruction signals to the central data processor for registering used codes can occur in accordance with the accuracy requirements, the allowable costs and the structure of the use, continuously on-line or batchwise (for instance, each time when the incoming morning

mail has been processed). The central data processor is arranged for controlling registration means 11 in response to the receipt of instruction signals indicating that marks corresponding with certain codes have been applied, these registration means 11 being coupled to the central data processor 3 for storing on the information carrier 4 the codes that correspond with applied marks.

[0014] Communication between the central processor 3 and the distributed local data processors 6 as well as between the distributed local data processors 6 and the associated mark assemblies 5 preferably proceeds in encrypted form, so that it is guaranteed that codes in respect of which it is reported that corresponding marks have been applied have in fact been applied and that no marks can be applied without the corresponding codes being registered at the central data processor.

[0015] Issuing codes and safeguarding the authenticity can be done, for instance, in broadly the same manner as described in European patent application with publication number 0 775 988 for the on-line settlement of franking amounts depending on postage applied. More particularly, upon request, in a protected manner, a number of codes can be furnished by the central authorities. Instead of charging amounts in accordance with applied postage, however, a temporary register with applied codes can be generated, which codes to be registered centrally are passed on to the central data processor 3 when a new set of codes is being applied for. Further, codes associated with applied marks are registered centrally in a protected carrier, so that later, if desired, it can be verified whether a mark on a document is real and whether a particular number of documents do indeed constitute the total of documents received, or at least registered, on a particular day. Because for a large part the same apparatuses as for franking can be used, it is particularly appealing to combine the registration of, for instance, received documents in the proposed manner with franking in a manner which is known from the European patent application mentioned.

[0016] Since the application of the marks is coupled automatically, without human intervention, to the registration of codes representing the applied marks, the registration of documents can be carried out very simply and be properly protected against unauthorized intervention. Preferably, data of contents are also coupled to the data to be registered. It is also possible, however, to store such data separately and optionally in a less well protected manner. In fact, the applied marks make it possible to prove afterwards whether a particular document is indeed the document to which the registration relates.

[0017] The proposed data processor structure with a central data processor unit 3 for generating unique codes, with a client-bound data processor unit 6 remote from the central data processor unit 3 and coupled to the marking assembly 5, and with communication

means 7, 8 coupled to the central data processor unit 3 and the client-bound data processor unit 6 for communication between the central data processor unit 3 and the client-bound data processor unit 6 via a communication network 2 then enables a registration of used codes that is particularly reliable and very effectively protected against modification or erasure.

[0018] Owing to the central data processor 3 being connected and arranged for cooperation with a plurality of distributed client-bound data processor units 6 which are operatively coupled to the central data processor unit 3, efforts towards the protected registration of codes represented by applied marks can be divided over a plurality of users, which limits the costs per user of the certification of document registration.

[0019] For achieving a protected registration, it is advantageous if each of the codes associated with a document is unique. It can thus be made substantially more difficult for any third party to predict what a mark for a document should look like without a code having been used for generating that mark.

[0020] For a reliable protection of the register of codes that are associated with applied marks, it is further advantageous if the registration means 11 are controlled exclusively by the central data processor unit 3. To that end, in the proposed data processor structure, the central data processor unit 3 is coupled between an associated one of said connections 12 and the registration means 11 for providing access to the registration means 11 exclusively via the central data processor unit 3. The central data processor unit 3 thus forms a shield against unauthorized access to the registration means.

[0021] Although the marking assembly 5 can be designed in many different ways, it is preferably designed as an electrostatic or inkjet printer, because such printers can be advantageously used for the computer-controlled printing of symbols with a high resolution. This last is of importance to be able to apply small symbols that still contain sufficient information to accommodate effectively encrypted information in them. The marking assembly 5 comprises a slot 13 through which an edge portion of a document to be marked can be passed for providing marks thereon. On opposite sides of the slot 13, transport rollers are arranged for controlling the feed-through speed of documents that are being marked. Such constructions are known in the field of franking machines.

[0022] Fig. 2 shows a system according to an alternative exemplary embodiment. In this system, the protected information carrier 24 and, coupled thereto, a data processor unit 23 of the data processor structure constitute a separate, protected unit as is known per se, for instance, in the field of electronic franking machines. As a result, a document registration which is better safeguarded and simple to carry out can be obtained without depending to that end on communication with the external world.

[0023] The system shown in Fig. 2 comprises an

envelope hopper 33 arranged for accommodating a row of standing envelopes and for feeding envelopes one by one to a transport structure with a transport path for serially transporting envelopes. This transport path is formed by a transport table 34 with driven and steerable transport rollers 35 and two transport stations 49, 50. The rollers 35 are coupled to driving and steering assemblies arranged for driving and steering the rollers 35, such that envelopes are displaced successively along a first side edge 36, a rear edge 37 and a second side edge 38.

[0024] Located along the first side edge 36, the rear edge 37 and the second side edge 38 are openers 39, 40, 41 for detaching front and rear panels of envelopes from each other along folding edges, which envelopes follow a path indicated by arrows 42, 43, 44.

[0025] Located downstream of the openers 39, 40, 41 is an extractor assembly 42 for removing documents from opened envelopes. This extractor has an exit 45 for discharging extracted documents and a discharge path 46 for discharging envelopes. A mail extractor as designated by reference numerals 33-46 and as described hereinabove is commercially available in the form of the Neopost IM 35 Eaziopener. For further details regarding such a mail extractor, reference is made to U.S. Patents 5,179,820; 5,175,979; 5,222,585; 5,336,034 and 5,415,266, the contents of which are to be considered incorporated herein.

[0026] According to this exemplary embodiment, the marking assembly 25 is located downstream of the extractor assembly along the transport structure, for providing extracted documents with marks. The extractor assembly further has an operating mode in which the envelopes, too, are discharged via the exit 45 for documents. This makes it possible, using the marking assembly 25, to provide envelopes with marks too.

[0027] The proposed system makes it possible, in operation, fully automatically, to automatically supply envelopes one by one from a row, along a transport path, to detach front and rear panels of each of the envelopes from each other in the transport path along three folding edges, to extract the contents from the envelope and to provide a mark on at least an envelope transported by the transport structure or a document removed therefrom. Thus, a considerable saving on labor is achieved and a very reliable guarantee of the registration of all received documents is achieved.

[0028] In order to ensure the authenticity of documents consisting of more than three pages as well, the mark could be applied so as to penetrate the documents, as by perforation. It is preferred, however, to bond the extracted documents together in sealed fashion, which is easier to realize especially in the case of thicker sets of documents and requires less complex and less powerful tools. To that end, the proposed system is provided, downstream of the extractor and the marking assembly, with a bonding station 47 for bonding the extracted documents together in a sealed fashion.

[0029] The marking assembly 25 is preferably further arranged for applying postage. To that end, the same protected registration structure can be used as for registering documents provided with marks. If such multiple use is not allowed by the postal authority in question, it is also possible to utilize a data processor structure of structurally analogous makeup with associated registration means and protected information carriers, which then still provides the advantage that the means for handling the postal items and for applying the marks can be used for two purposes. It is, in particular, of importance here that the activity of registering documents in businesses typically occurs in the morning (after the mail has come in), while franking typically occurs at the end of a working day (shortly before postal items prepared during the day are dispatched). Even if the proposed apparatus were not provided with a data processor structure and associated registration means and information storage means for registering documents, combining a device for opening or extracting mail with a franking apparatus arranged along the transport path of that device is advantageous, because for both functions use can be made of the same means for transporting postal items one by one and because the two functions, as set out hereinabove, typically occur during different parts of the day.

[0030] If a wholly independent franking unit is used, it is advantageous to design it as a module that can be arranged as a replacement of one of the openers 39-41.

[0031] In order not to cut open envelopes to be franked and not to extract the documents therein, the openers 39-41 and the extractor 42 are adapted for deactivation, so that the envelopes, during franking, pass unhindered along the openers 39-41 and the extractor, and are carried via document exit 45 of the extractor 42 to the marking assembly.

[0032] For operating both the franking function and the registration function, the data processor unit 23 is coupled to a keyboard 29 and a display 30.

[0033] To automatically register data regarding the contents of extracted documents as well, further a scanner 48 is included downstream of the extractor 42, which scanner 48 is arranged for passing and scanning documents (and/or optionally envelopes) supplied from the exit 45. The scanner 48 is coupled to the data processor unit 25 for transferring scanning results which can be supplied by the data processor unit 25 to a registration structure for storing scanning results in the protected memory 24.

[0034] To afford protection against the mark being copied, the data processor unit 23 may, for instance, be arranged for preventing the same code being issued twice. Further, the marking assembly may be designed as a printer capable of applying marks protected against reproduction, for instance by making use of magnetizable ink in combination with a magnetization pattern, ink that cannot be copied, or a mechanical seal which in turn carries the mark.

[0035] For further enhancing the protection of the authenticity of registered documents, the codes are preferably generated depending on the information content of the document to be registered. To that end, the codes can be generated, for instance, by encryption of the date of receipt in combination with the first three letters of the document or particular properties of the printing pattern of the document in question.

[0036] These data can be obtained in different ways. It is possible, for instance, to input them via the keyboard 29. Preferably, however, recording data needed for determining the code is also automated, by scanning the document to be registered at least partly in the scanner 48 and supplying data regarding scanning results generated by the scanner 40 to the data processor unit 23. Thus, registration codes for the documents to be registered can be determined depending on the scanning results obtained upon scanning.

[0037] For protecting the data regarding the contents of the documents, it is advantageous if, using an asymmetrical keying system (encryption system), the scanning results are each processed in accordance with a processing key and are read back using an associated read-back key which is different from said processing key. The read-back key may, for instance, be coupled to the mark applied on the document in question and/or to the associated code. Other ways for certifying the authenticity of digital documents may be used, such as generating digital certificates, digital signatures and/or digital time stamps. Further, it is also possible to provide a mark representing the code in question, not on the registered document, but exclusively on a copy in digital or analog, or electronic or physical form. In that case, too, the advantage is obtained that in response to the application of the mark, the associated code is automatically registered. Such a mark can be incorporated, for instance, in data representing the image of the document. Verification can then occur, for instance, by defining a 7 on the basis of a part of the mark that provides for human visual representation of the code, which verification key must match the stored and processed data representing the image of the document.

Claims

1. A system for registering existing, physical documents, comprising:

a data processor structure (3, 6; 23) arranged for determining codes;

a marking assembly (5; 25) coupled to said data processor structure (3, 6; 23), for providing each document to be registered, or a physical or digital representation thereof, with at least one mark which represents one of the codes;

a protected information carrier (4; 24); and registration means (11) coupled to said data

processor structure (3, 6; 23), for registering a code of said codes that corresponds with at least one applied mark, on or in said information carrier (4; 24) in response to the application of said at least one mark.

2. A system according to claim 1, wherein said data processor structure (3, 6) comprises a central data processor unit (3) for generating unique codes, and a client-bound data processor unit (6) remote from said central data processor unit (3) and coupled to said marking assembly (5), and further comprising communication means (7, 8) coupled to said central data processor unit (3) and said client-bound data processor unit (6) for transfer of data between said central data processor unit (3) and said client-bound data processor unit (6).
3. A system according to claim 2, further comprising a plurality of distributed ones of said client-bound data processor units which in operating condition are coupled to said central data processor unit (3).
4. A system according to claim 2 or 3, wherein said client-bound data processor units (6) and said central data processor unit (3) are each located behind an associated connection (12) to a communication network (2), and wherein said central data processor unit (3) is coupled between an associated one of said connections (12) and said registration means (11) for providing access to said registration means (11) exclusively via said central data processor unit (3).
5. A system according to any one of claims 1-3, wherein said protected information carrier (24) and, coupled thereto, at least one data processor unit (23) of said data processor structure (23) form a separate, protected unit.
6. A system according to claim 5, further comprising a scanner (48) for scanning said documents, which scanner (48) is coupled to said data processor structure (23) for transferring scanning results.
7. A system according to claim 6, wherein said data processor structure (23) is arranged for generating said codes depending on said scanning results.
8. A system according to claim 6 or 7, wherein said data processor structure (23) is arranged for processing said scanning results depending on said codes and for reading back processed scanning results associated with a document, using an associated read-back key which is not suitable for carrying out said processing.
9. A system according to any one of the preceding

claims, further comprising:

a transport structure (34, 49, 50) with at least one transport path (34) for serially transporting envelopes, and

at least one opener (39, 40, 41) located along the transport path (34) for detaching front and rear panels of envelopes from each other in the transport path (34) along at least one folding edge,

wherein the marking assembly (25) is located along said transport structure (34, 49, 50) for providing with marks at least envelopes transported by the transport structure (34, 49, 50) or documents removed therefrom.

10. A system according to claim 9, further comprising an extractor (42) located downstream of the opener (39, 40, 41), for extracting documents from opened envelopes.

11. A system according to claim 10, wherein the marking assembly (5; 25) is located downstream of the extractor (42).

12. A system according to claim 10 or 11, further comprising a bonding station (47) downstream of the extractor, for bonding extracted documents together in sealed fashion.

13. A system according to any one of the preceding claims, further comprising a protected memory (3; 24) for storing postage value positions.

14. A system according to any one of the preceding claims, wherein the marking assembly (5; 25) is further arranged for applying postage.

15. A system according to any one of the preceding claims, wherein the marking assembly (5; 25) is designed as a printer.

16. A system according to any one of the preceding claims, further comprising an envelope supply structure (33) for serially feeding envelopes from a stack to the transport structure (34, 49, 50).

17. A method for registering existing, physical documents, comprising:

the step of a data processor structure (3, 6; 23) determining a code in each case;
actuating a marking assembly (5; 25) for applying at least one mark, which represents said code, on each document to be registered;
in response to the application of said at least one mark, the step of the data processor structure (3, 6; 23) actuating registration means

(11); and

registering accordingly data corresponding with said code on a protected information carrier (4; 24).

18. A method according to claim 17, wherein each of said codes associated with a document is unique.

19. A method according to claim 17 or 18, wherein said codes are generated in a central data processor unit (3) and are sent to a client-bound data processor unit (6) remote from said central data processor unit, which client-bound data processor unit actuates said marking assembly (5; 25) for applying said mark.

20. A method according to claim 19, wherein said central data processor unit (3) sends codes to a plurality of said client-bound data processor units (6).

21. A method according to claim 19 or 20, wherein said registration means (11) are controlled exclusively by said central data processor unit (3).

22. A method according to any one of claims 17-21, wherein the document to be registered is at least partly scanned, and wherein data regarding scanning results generated by the scanner (48) are stored on said protected information carrier (24).

23. A method according to any one of claims 17-22, wherein the codes are generated depending on the information content of the document to be registered.

24. A method according to claim 23, wherein the document to be registered is at least partly scanned, wherein data regarding scanning results generated by the scanner are supplied to the data processor structure (23) and wherein determining the codes is carried out at least partly depending on a supplied scanning result.

25. A method according to claim 22 or 24, wherein said scanning results are each processed in accordance with a processing key and are read back with the aid of an associated read-back key which is different from said processing key.

26. A method according to claim 25, wherein said code determines said read-back key.

27. A method according to any one of claims 17-26, further comprising:

serially transporting envelopes along a transport path (34),
detaching front and rear panels of each of the

envelopes in the transport path (34) from each other along at least one folding edge, and applying a mark to at least one opened envelope or a document removed therefrom.

5

28. A method according to claim 27, further comprising extracting a document from each of the envelopes.

29. A method according to claim 27 or 28, further comprising the bonding together of extracted documents in sealed fashion.

10

15

20

25

30

35

40

45

50

55




Fig. 1




Fig. 2



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 20 4464

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	FR 2 730 575 A (PITNEY BOWES) 14 August 1996 * abstract; claim 1 *	1,17	B43M7/02 G07B17/04 G06F17/60
A	US 4 791 281 A (JOHNSEN EDWARD L ET AL) 13 December 1988 * abstract; claim 1 *	1,17	
A	US 3 890 599 A (SIMJIAN LUTHER G) 17 June 1975 * abstract; claim 1 *	1,17	
E	WO 98 19258 A (ELECTRONIC DATA SYST CORP) 7 May 1998 * abstract * * page 6, line 1 - page 7, line 15 *	1,17	
D,A	EP 0 775 988 A (NEOPOST IND) 28 May 1997 * abstract *	14,15	
D,A	US 5 336 034 A (HIDDING GERHARD) 9 August 1994 * abstract *	9-12, 27-29	TECHNICAL FIELDS SEARCHED (Int.Cl.6) B43M G07B G06F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 4 May 1999	Examiner Suendermann, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 20 4464

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-05-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2730575	A	14-08-1996	US 5717596 A	10-02-1998
US 4791281	A	13-12-1988	NONE	
US 3890599	A	17-06-1975	NONE	
WO 9819258	A	07-05-1998	AU 3896897 A	22-05-1998
EP 0775988	A	28-05-1997	US 5822738 A	13-10-1998
US 5336034	A	09-08-1994	NL 9102011 A	16-06-1993
			DE 69204262 D	28-09-1995
			DE 69204262 T	02-05-1996
			EP 0545480 A	09-06-1993

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

